

## Spool Application

Wire Diameter, in.	Materials	Temper	Standard Spools
<b>Round Wire:</b>			
Samples	All	All	<a href="#"><u>CFW 50</u></a>
0.0002" - 0.001"	All	All	<a href="#"><u>CFW 101</u></a> <a href="#"><u>AL-8</u></a> <a href="#"><u>TS-1</u></a> <a href="#"><u>CFW 400</u></a>
0.0007" – 0.003"	Bonding Wire	All	<a href="#"><u>AL-8</u></a> <a href="#"><u>AL-9</u></a> <a href="#"><u>TS-1</u></a> <a href="#"><u>AL-22</u></a>
0.001" – 0.020"	Precious Metals	All	<a href="#"><u>CFW 400</u></a> <a href="#"><u>CFW 103</u></a>
0.001" – 0.010"	Non-Precious	Annealed, S/R	<a href="#"><u>CFW 103</u></a> <a href="#"><u>CFW 300</u></a> <a href="#"><u>CFW 500</u></a>
0.001" – 0.010"	Non-Precious	Hard	<a href="#"><u>CFW 500</u></a> <a href="#"><u>CFW 400</u></a>
0.010" – 0.040"	Non-Precious	All	<a href="#"><u>CFW 500</u></a> <a href="#"><u>CFW 500T</u></a> <a href="#"><u>CFW 600</u></a> <a href="#"><u>CFW 600T</u></a> <a href="#"><u>CFW 812</u></a>
> 0.040"	Non-Precious	All	<a href="#"><u>CFW 812</u></a> <a href="#"><u>CFW 600</u></a> <a href="#"><u>CFW 600T</u></a>
0.020" – 0.064"	SS, Music Wire	Hard or Spring	<a href="#"><u>CFW 812</u></a>
. 0.080" & larger	Non-Precious	All	Coil <a href="#"><u>CFW 812</u></a>
<b>Flat Wire:</b>			
<0.025" wide	Non-Precious	All	<a href="#"><u>CFW 103</u></a> <a href="#"><u>CFW 500</u></a>
0.025" - 0.050" wide	Non-Precious	All	<a href="#"><u>CFW 500</u></a>
0.050" & wider	Non-Precious	All	<a href="#"><u>Pancake</u></a> <a href="#"><u>CFW 500</u></a>

Note: Specified quantity/spool will affect the choice of spool type.

*[Underline indicates link to photo & additional spool information.]*